This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

IN THE CLAIMS:

Please amend claims 1 and 6 as shown and cancel claims 7 and 8 without prejudice.

- 1. (Currently amended) A process for the coating of a wooden, wooden wood-like and/or cellulose-containing substrate comprising the steps of:
 - a) applying a press coating to the substrate;
 - applying heat and pressure to the coated substrate to cure the press coating and to obtain a substrate with a smooth coating film, with the pressure being such that the substrate is not substantially compressed;
 - c) applying a top coat to the substrate after the curing of the press coating; and
 - d) curing said top coat.
- 2. (Original) The process according to claim 1, wherein in an additional step before the top coat is applied, a primer coating is applied and cured.
- 3. (Original) The process according to claim 1, wherein all process steps are performed on a single production line.
- 4. (Original) The process according to claim 1, wherein the top coat is a radiation curable top coat and the radiation curable top coat is cured using UV radiation.
- 5. (Original) The process according to claim 1, wherein before the top coat is applied, a printing is applied on the substrate and the top coat is applied on top of said printing.
- 6. (Currently amended) The process according to claim 1, wherein the press coat is a aqueous colloidal dispersion comprising:
- _____particles of a polymer of an ethylenically unsaturated monomer, and
 _____ 40 60 wt.%, based on the total_weight, weight of the emulsion solids, of filler and/or pigment.
- 7. (Cancelled)
- 8. (Cancelled)